

SENTRY

# Rugged, Dual-Sensor PTZ System

INFINITI ELECTRO-OPTICS

The Sentry is a modular multi-sensor PTZ that can be configured with our long range visible, ZLID™, and thermal camera options. These include our 4K/8 Megapixel 20-1225mm 61X zoom day/night camera, thermal imaging cameras up to 460mm, and up to 4km of ZLID™ illumination.

Combining these multiple sensors allows for accurate detection, recognition, and identification of potential threats. Active deterrence measures such as LRADs, spotlights, and laser dazzlers can also be integrated to ensure threats are not just detected, but mitigated.

The Sentry's strengthened aluminum construction and rugged IP66 housings use anti-corrosive coatings, allowing it to withstand the harshest climates for dependable perimeter security, mobile/marine vessels, homeland defense, and coastal protection.

## Key Features:

- › Multi-Sensor Visible and Thermal Integrated PTZ System
- › HD or UHD Progressive Scan CMOS Day/Night IP Camera
- › Long-Range Visible Zoom Options from 36X to 95X
- › Visible/NIR Field of View Options from 75° to 0.36°
- › 12µm 640×512 VOx Uncooled Thermal Imager or Optional SD or 1280×1024 HD Cooled Thermal Imager
- › Uncooled VOx Thermal Imaging Options up to 310mm
- › SD and HD Cooled Thermal Options up to 460mm
- › Up to 21km Human Detection and 52km Vehicle Detection with Thermal (using Johnson Criteria DRI standards)\*
- › Endless 360° Pan and ±90° Tilt, with pan speeds up to 60°/s
- › IP66 Military-Grade Design with Military Cable Connectors
- › Designed for Fixed, Marine or Mobile Applications



Appearance will vary based on configuration options.

6mm-**218**  
36X 8MP

5.6mm-**272**  
49X 8MP

15mm-**800**  
53X 4MP

15mm-**800**  
53X 8MP

10.6mm-**1015**  
95X 8MP

20mm-**1225**  
61X 8MP

Multiple Zoom Lens Options up to 1225mm

20mm-**105**  
LWIR

25mm-**130**  
LWIR

32mm-**155**  
LWIR

34mm-**185**  
LWIR

26mm-**230**  
LWIR

Uncooled Thermal Zoom up to 230mm

18mm-**230**  
MWIR<sup>HD</sup>

16mm-**305**  
MWIR<sup>HD</sup>

21mm-**430**  
MWIR<sup>HD</sup>

30mm-**460**  
MWIR<sup>HD</sup>

Optional Cooled Thermal

1km  
ZLID™

2km  
ZLID™

3km  
ZLID™

4km  
ZLID™


Optional Long-Range IR Illumination

OCTAGON ENABLED ✓  
Advanced Control

Military Connectors

Mobile & Marine Ready

Weatherproof Construction



View the Sentry on our website:

# THE SENTRY'S Visible/NIR HD Zoom Camera





## VIS/NIR Optical Camera

Infiniti's VIS/NIR zoom cameras utilize high-end CMOS sensors to offer excellent spectral sensitivity in the visible and near-infrared wavelengths of light to provide high-quality images optimized for long-range surveillance. They are designed to provide industry-leading performance and quality, with image resolutions ranging from 2MP (1080p HD) to 8MP (4K UHD). Precision engineered IR-corrected continuous zoom lens options offer a range of focal lengths with up to 95X optical zoom and integrated rapid autofocus to allow for long-range surveillance of targets without operator intervention.

## Wide Angle Spotters

The Sentry PTZ can also support our optional wide angle spotter cameras for both visible and thermal. By integrating a second sensor with a wide angle lens, operators can maintain wide area situational awareness while simultaneously achieving detailed surveillance of targets at extreme long ranges.



**Standard Color Visible Image**  
(Optical Fog Filter Disabled)

**NIR Image**  
(Optical Fog Filter Enabled)

## Optical Fog Filter (NIR Only Mode)

While all of our sensors offer a nighttime NIR + visible mode for optimized sensitivity in low light, the cameras equipped with our NIR bandpass filter (also referred to as a "fog filter") allow users to isolate the NIR (near-infrared) wavelength of light during the day for clearer long-range daytime imaging.

Long-range imaging needs to see through large amounts of atmosphere which often contains particulates like smoke, haze/fog, and other atmospheric distortions. Cutting out the visible wavelength and isolating the NIR can mitigate the effects of smoke, haze and light fog, producing an image with better contrast and less distortion. Our optical fog filter lenses incorporate a motorized filter that is used with the camera's monochrome mode and de-haze image processing to see through smoke, smog and haze.

# THE SENTRY'S Night Vision Technologies



## See in the Dark with ZLID™

IR (infrared) illumination allows for detailed video when there isn't enough natural light, however typical IR LED illuminators have very limited ranges. For longer-range illumination, a laser is needed. Many laser illuminators overexpose the center of the screen and leave the edges dark. Infiniti's ZLID™ (Zoom Laser IR Diode) technology synchronizes the IR intensity and area illumination with the zoom lens for outstanding active IR performance, eliminating over-exposure, washout, and hot-spots for clear images in complete darkness.



## See Further with Thermal

Thermal cameras use naturally emitted heat to create their image. This means that no light source is needed, and thermal imaging performance works just as effectively in bright daylight as it does in complete darkness. Additionally, since humans, animals, and vehicles are usually warmer than their surroundings, thermal imaging renders these objects much brighter which makes them easy to spot, even when hiding in the shadows. Thermal images are also unaffected by headlights or spotlights and can see through atmospheric obstructions such as smoke, dust, and light fog. This makes thermal imaging an ideal technology for many applications including surveillance and security, search and rescue, fire fighting, marine and land navigation, wide area situational assessment, and much more.

The Sentry boasts industry-leading thermal cameras with uncooled LWIR and cooled MWIR resolution options of either 640×480 SD or 1280×1024 HD to ensure mission success.



# Thermal Imaging Options: Cooled vs Uncooled

## Uncooled Long Wave Infrared (LWIR)

Infiniti uses cutting-edge 12µm LWIR VOx uncooled thermal sensors with resolutions up to 1280x1024 HD. The 12µm pixel pitch provides a narrower field of view without changing the lens, allowing it to achieve 40% further range than 17µm sensors.

These sensors are paired with large aperture lenses of  $f/1.0$ - $f/1.3$ , compared to the standard  $f/1.5$ - $f/1.6$ , allowing up to 2.3 times more heat to reach the sensor. This results in higher sensitivity, sharper images, and longer ranges, making LWIR one of the most cost-effective long-range imaging solutions.


## Cooled Mid-Wave Infrared (MWIR)

Infiniti offers cooled thermal in SD or HD options. Our 15µm 640x480 InSb or MCT sensors are comparable to the standard MWIR offerings in the industry. Our 10µm 1280x1024 HD X-Hot sensor provides 400% higher resolution and 50% longer range than traditional 15µm sensors. This means a 400mm lens on our X-Hot sensor is equivalent to a 600mm lens on a traditional 15µm sensor allowing it to provide a narrower angle (further zoom) for more detail at long distances.


MWIR sensors use integrated cryo-coolers to cool the sensors down to  $-196^{\circ}\text{C}$  (InSb) or  $-123^{\circ}\text{C}$  (X-Hot). This exponentially increases the sensitivity of the thermal camera, allowing MWIR cameras to use smaller and more powerful lenses than uncooled LWIR cameras, however the cryo-coolers do require maintenance at intervals that vary depending on sensor type and environment.

Our new **Thermally Compensated Optics (TCO)** technology maintains MTF, back focal distance, and effective focal length across a wide range of operating temperatures. This TCO technology effectively mitigates challenges posed by thermal expansion. Paired with our HD InSb or X-HOT MWIR thermal cores, Infiniti's systems provide high contrast and ultra long distance infrared imaging for mission critical applications such as threat detection, surveillance, auto-tracking and targeting. With lens options capable of detection ratings\* over 55km (based on DRI ratings in ideal conditions), the Arc is the ultimate thermal surveillance platform.

### Human DRI:



### Vehicle DRI:



**DETECTION\***  
 **RECOGNITION\***  
 **IDENTIFICATION\***

\*DRI detection ratings are based on industry-wide standards (Johnson's Criteria) that can be misleading if not properly understood. For more information, please see our whitepaper about understanding DRI measurements at: [www.infinitioptics.com/dri](http://www.infinitioptics.com/dri)

# Visible Camera Options

		8M-61X-OS	8M-95X	8M-53X (-OS)	4M-53X (-OS)	8M-49X	8M-36X	3M-49X	4M-36X
Simulated FOV @ 1km									
Pixels Per Meter @ 1km		612ppm	508ppm	400ppm	274ppm	136ppm	109ppm	78ppm	75ppm
DORI	D: 25ppm	24,500m Detection	20,300m Detection	16,000m Detection	10,944m Detection	5,440m Detection	4,360m Detection	3,103m Detection	2,982m Detection
	O: 62ppm	9,879m Observation	8,815m Observation	6,452m Observation	4,413m Observation	2,194m Observation	1,758m Observation	1,251m Observation	1,202m Observation
	R: 125ppm	4,900m Recognition	4,060m Recognition	3,200m Recognition	2,189m Recognition	1,088m Recognition	872m Recognition	621m Recognition	596m Recognition
	I: 250ppm	2,450m Identification	2,030m Identification	1,600m Identification	1,094m Identification	563m Identification	436m Identification	310m Identification	298m Identification
Output Resolution		8MP/4K @ 30fps (3840x2160)	8MP/4K @ 30fps (3840x2160)	8MP/4K @ 30fps (3840x2160)	4MP @ 30fps (2688x1520)	4K @ 30fps (3840x2160)	8MP/4K @ 30fps (3840x2160)	3MP @ 55fps (2048x1536)	4MP @ 60fps (2688x1520)
Image Sensor		8.4 Megapixel 1/1.8" W CMOS	8.4 Megapixel 1/1.8" W CMOS	8.4 Megapixel 1/1.8" W CMOS	4.1 Megapixel 1/1.7" W CMOS	8.4 Megapixel 1/1.8" W CMOS	8.4 Megapixel 1/1.8" W CMOS	3.2 Megapixel 1/1.8" CMOS w/GS <sup>++</sup>	4.5 Megapixel 1/1.7" W CMOS
Lens*	Focal Length	20-1225mm	10.6-1015mm	15-800mm	15-800mm	5.6-272mm	6-218mm	5.6-272mm	6-218mm
	Optical Zoom	61X Optical Zoom x 16X Digital	95X Optical Zoom x 16X Digital	53X Optical Zoom x 16X Digital	53X Optical Zoom x 16X Digital	49X Optical Zoom x 16X Digital	36X Optical Zoom x 16X Digital	49X Optical Zoom x 16X Digital	36X Optical Zoom x 16X Digital
	Angle of View	21°-0.36° Horizontal	42°-0.43° Horizontal	28°-0.55° Horizontal	29°-0.56° Horizontal	75°-1.62° Horizontal	65.2°-2° Horizontal	71.4°-1.51° Horizontal	66.4°-2.1° Horizontal
	1080p Equiv. <sup>†</sup>	122X, 0.18° HFOV	190X, 0.22° HFOV	106X, 0.28° HFOV	74X, 0.4° HOV	98X, 0.81° HFOV	72X, 1.01° HFOV	52X, 1.42° HFOV	50X, 1.48° HFOV
	Focus	Auto / Manual	Auto / Manual	Auto / Manual	Auto / Manual	Auto / Manual	Auto/Manual	Auto/Manual	Auto/Manual
Minimum Illumination (Color / Black & White)		0.1 Lux / 0.01 Lux @ f/2.1	0.1 Lux / 0.01 Lux @ f/2.1	0.1 Lux / 0.01 Lux @ f/1.5	0.05 Lux / 0.005 Lux @ f/2.8	0.05 Lux / 0.005 Lux @ f/1.4	0.1 Lux / 0.01 Lux @ f/1.5	0.005 / 0.001 Lux @ f/1.4	0.005 / 0.0005 Lux @ f/1.5
Optical Fog Filter (NIR)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Heatwave Mitigation		Yes	Yes	Yes	Yes	No	No	No	No
NDAA Compliant		Yes	No	Yes	No	Yes	Yes	No	Yes
Video Network	Compression	H.265/H.264/MJPEG							
	Protocol	ONVIF, HTTP, RTSP, RTP, TCP, UDP							
Image Stabilization		Optical & EIS	Electronic (EIS)	EIS, Optional Optical Stabilization		Electronic Image Stabilization (EIS)			
Image Enhancements		White Balance, WDR, 2D/3D DNR, BLC, HLC, Digital Defog							
Edge Storage		Supports MicroSD Card up to 256GB							

\*Lens measurements, angle of view and PPM/DORI numbers are accurate to ±10% due to back focus distances, sensor sizes, lens manufacturing, etc. †Zoom ratio and FOV equivalent if zooming into a 1080p crop of the video output. ††Global shutter.

## LED & ZLID™ Illumination Options

	500m IR LED	750m ZLID		1km ZLID		1.5km ZLID		2km ZLID		3km ZLID		4km ZLID	
Illumination Distance	500m	750m		1000m		1500m		2000m		3000m		4000m	
Wavelength	808nm	808nm	940nm	808nm	940nm	808nm	940nm	808nm	940nm	808nm	940nm	808nm	940nm
NOHD	0m (eye safe)	13m	9.6m	50m	36.6m	56.4m	45.2m	69m	51m	238m	175m	266m	196m

# Thermal Camera Options

## Uncooled Thermal Camera Options

	26-75mm (-75TIZ)	20-105mm (-105TIZ)	25-130mm (-130TIZ)	32-155mm (-155TIZ)	34-185mm (-185CTZ)	26-230mm (-230TIZ)												
Image Sensor	Uncooled Vanadium Oxide (VOx) Microbolometer, 30Hz																	
Resolution	640x512/640x480 pixels (1280x1024 optional)																	
Pixel Pitch	12µm (Over 200% further range than 25µm sensors, 40% further range than 17µm sensors)																	
Lens (Motorized Zoom)	26-75mm f/1.0	20-105mm f/1.2	25-130mm f/0.8-f/1.2	32-155mm f/1.2	34-185mm f/1.2	26-230mm f/1.3												
Focus	Motorized Autofocus																	
Field of View	640x512	16.8°-5.86° Horizontal FOV	21.7°-4.19° Horizontal FOV	17.5-3.38° Horizontal FOV	13.7°-2.8° Horizontal FOV	12.9-2.38° Horizontal FOV	16.8-1.91° Horizontal FOV											
	1280x1024	32.9-11.7° Horizontal FOV	Not Available	34.2-6.76° Horizontal FOV	27.0-5.67° Horizontal FOV	25.5-4.75° Horizontal FOV	32.9-3.82° Horizontal FOV											
Pixels Per Meter @ 1km	6.25ppm	8.8ppm	10.8ppm	12.9ppm	15.4ppm	19.2ppm												
Human DRI Ratings*	2.9 km	988 m	494 m	4.1 km	1.3 km	693 m	5.1 km	1.7 km	858 m	6.1 km	2.0 km	1.0 km	7.3 km	2.4 km	1.2 km	9.0 km	3.0 km	1.5 km
Vehicle DRI Ratings*	7.1 km	2.3 km	1.2 km	10.0 km	3.3 km	1.6 km	12.4 km	4.1 km	2.0 km	14.8 km	4.9 km	2.4 km	17.7 km	5.9 km	2.9 km	22.0 km	7.3 km	3.6 km
Image Optimizations	DICE, BPR, NUC, & AGC user configurable via API																	
Digital Zoom	2X & 4X dynamic zoom/pan with range switching																	
Spectral Range	LWIR (7,000-14,000nm)																	
Thermal Sensitivity	50mK																	
Cooler Lifetime	No cooler required																	
Image Display Modes	White Hot, other color palettes available upon request																	

## Cooled Thermal Camera Options

	15-235mm (-235CTZ)	30-430mm (-430CTZ)	18-230mm (-230CTZ-HD)	16-305mm (-305CTZ-HD)	33-430mm HD (-430CTZ-HD)	30-460mm HD (-460CTZ-HD)												
Image Sensor	High-Sensitivity Cooled X-Hot Detector, 30Hz		High Sensitivity Cooled InSb or X-Hot Sensor, 30Hz															
Resolution	640x480 or 640x512 pixels		1280x1024 pixels															
Pixel Pitch	10µm (50% further range than 15µm sensors)		10µm (50% further range than 15µm sensors)															
Lens (Motorized Zoom)	15-235mm f/3.6	30-430mm f/3.6	18-230mm f/4.0 w/TCO	16-305mm f/4.0 w/TCO	33-430mm f/4.0 w/TCO	30-460mm f/4.0 w/TCO												
Focus	Motorized Autofocus																	
Field of View	24.1-1.56° Horizontal FOV	12.2-0.85° Horizontal FOV	39.1-3.19° Horizontal FOV	43.6-2.4° Horizontal FOV	21.9-1.71° Horizontal FOV	24.1-1.59° Horizontal FOV												
Pixels Per Meter @ 1km	23.5ppm	43ppm	23ppm	30ppm	43ppm	46ppm												
Human DRI Ratings*	11.1 km	3.7 km	1.8 km	20.3 km	6.8 km	3.4 km	10.9 km	3.6 km	1.8 km	14.4 km	4.8 km	2.4 km	20.4 km	6.8 km	3.4 km	21.8 km	7.2 km	3.6 km
Vehicle DRI Ratings*	27.0 km	9.0 km	4.5 km	49.4 km	16.4 km	8.2 km	26.4 km	8.8 km	4.4 km	35.0 km	11.7 km	5.8 km	49.4 km	16.4 km	8.2 km	52.9 km	17.6 km	8.8 km
Digital Zoom	4X Digital Zoom (16X optional)																	
Spectral Range	3,000-5,000nm (MWIR)																	
Thermal Sensitivity	20-25mK																	
Cooler Lifetime (@23°C)	20,000 Hour Rated MTBF (InSb) / 30,000 Hour Rated MTBF (X-Hot)																	

\* **D R I** While DRI ratings are based on the industry-standard Johnson's Criteria, they represent theoretical maximums under ideal conditions that typically exceed real-world performance. Additionally, a "Detection" rating means that a target will appear only as a tiny speck of pixels, rather than as a clearly defined or recognizable object. For more info, please see our whitepaper about understanding DRI at: [www.infiniioptics.com/dri](http://www.infiniioptics.com/dri)

Focal lengths and FOVs are within ±5%.

# SENTRY

## Other Specifications



### Pan/Tilt Mechanical

Pan Angle & Speed	Endless 360° Continuous Rotation, 0.1° to 60°/s (speeds may differ depending on configuration)
Tilt Angle & Speed	-45° to +45° (full ±90° optional, requires pedestal; required tilt range will determine the size of the pedestal), 0.1° to 30°/s (speeds may differ depending on configuration)
Proportional Pan/Tilt	Auto adjusts pan/tilt speed based on zoom level
Octagon Enabled	Infiniti's Octagon platform provides a unified API for integration with third party C2/VMS softwares, radar slew-to-cue, and our network-based PTZ control accessories.

### Physical

Construction	High Strength Aluminum Alloy
--------------	------------------------------

### Environmental

Operational Temperature	-20°C to +60°C (-40°C optional), <90% Relative Humidity
Environmental	IP66 Weatherproof Housing

### Electrical

Input Voltage	48VDC (24V optional)
Power Consumption	40W to 350W, depending on configuration and heater

**Optional Features:** LRF (Laser Rangefinder), Wide-Angle 4K Spotter Camera, Reflective Paint or Customized Paint Finish, Joystick (Pelco-D or IP 3-axis joysticks), Solar Power, Wireless Analog or IP Radios P2P or mesh

Brochure specifications subject to change.



SENTRY

# Additional Images



[WWW.INFINITIOPTICS.COM](http://WWW.INFINITIOPTICS.COM)

1-866-969-6463

[INFO@INFINITIOPTICS.COM](mailto:INFO@INFINITIOPTICS.COM)